PH BENCH METER

Model: PH-202 *ISO-9001, CE, IEC1010*



FEATURES

- * General purpose pH measurement.
- * Easy operation, compact size.
- * Water resistance on the front panel.
- * Application : Education, School, Laboratory, Industrial and Quality control.
- * Display: LCD, 18 mm digit height.
- * Range and Resolution: 0 to 14 pH x 0.01 pH
- * High Input Impedance
- * No adjustment for pH range Temp. Compensation.
- * pH electrode Any connector pH Electrode with BNC connector.





The Art of Measurement

PH BENCH METER

Model: PH-202

| GENERAL SPECIFICATIONS | | |
|------------------------|---|--|
| Features | * General purpose pH measurement. | |
| | * Easy operation, compact size. | |
| | * Water resistance on the front panel. | |
| | * Application : Education, School, Laboratory, Industrial | |
| | and Quality control. | |
| Display | LCD, 18 mm (0.7") digit height. | |
| Measurement | рН | |
| Range/ | 0 to 14 pH x 0.01 pH | |
| Resolution | | |
| Accuracy | 0.07 pH (pH5 to pH 9) | |
| | 0.1 pH (pH 4 to pH 10) | |
| | 0.2 pH (pH 1 to pH 3.9, pH 10.1 to pH 13) | |
| | * Main instrument only. | |
| Input Impedance | 10 ohms. | |
| PH range Temp. | No adjust. | |
| Compensation | ivo dajast. | |
| Sampling Time | Approx. 0.4 second. | |
| Operating Temp. | 0 to 50 °C (32 to 122°F) | |
| Operating | Less than 80% RH. | |
| Humidity | | |
| Calibration Knob | External PH 4 (slope adj.) & PH 7 (Cal. adj.). | |
| Power Supply | 006P DC 9V battery. | |
| Power | Approx. 2.0 mA. | |
| Consumption | | |
| Dimension | 147 x 117 x 45 mm, | |
| | (5.8 x 2.6 x 4.0 inch). | |
| Weight | 250 g/0.55 LB. | |
| PH electrode | Any connector PH Electrode with | |
| (Optional) | BNC connector. | |
| Standard | Instruction Manual1 PC. | |
| Accessories | | |
| Optional | pH electrode. | |
| Accessories | pH 4.0 buffer solution, pH 7.0 buffer solution. | |

| APPLICATIONS | | |
|--------------------|----------------------|--|
| * AQUARIUMS | * FOOD PROCESSING | |
| * BEVERAGE | * PHOTOGRAPHY | |
| * FISH HATCHERIES | * LABORATORY | |
| * PAPER INDUSTRY | * SCHOOLS & COLLEGES | |
| * PLATING INDUSTRY | * SWIMMING POOLS | |
| * QUALITY CONTROL | * WATER CONDITIONING | |

| OPTIONAL ACCESSORIES | | |
|----------------------|---|--|
| pH ELECTRODE | General purpose pH electrode with BNC conector. | |
| PE-03 | Range: 1 to 13 pH (typical 0 to 14 pH). | |
| | Expoxy body, Body size: 12 mm dia. x 160 mm. | |
| | Cable length: 1 meter. | |
| pH ELECTRODE | General purpose & high quality pH electrode with BNC conector. | |
| PE-11 | Range: 1 to 13 pH (typical 0 to 14 pH). | |
| | Expoxy body, Body size: 9.5 mm dia. x 120 mm. | |
| | Cable length: 2 meter. | |
| pH ELECTRODE | Professional, laboratory & | |
| PE-01 | field usage. 9.5 mm dia. x 130 mm. | |
| | Epoxy body, 0 - 14 pH. | |
| | Cable length: 1 meter. | |
| SPEAR TIP | The "Spear Tip pH electrode " is perfect for those pH | |
| PH ELECTRODE | measurements in applications where sample piercing is required. | |
| Model: PE-04HD | Meat, sausage and cheese are ideal applications. The electrode | |
| | features a very durable glass measuring spear packaged in a | |
| | rugged virtually unbreakable epoxy body. | |
| | Measuring range: 0 to 14 pH. | |
| | Size 12 mm dia. x 150 m. | |
| BUFFER SOLUTION | PH 7.00 standard buffer solution. | |
| PH-07 | | |
| BUFFER SOLUTION | PH 4.00 standard buffer solution. | |
| PH-04 | CAT 0200 NI200 | |

 $^{^{\}star}$ Appearance and specifications listed in this brochure are subject to change without notice.