

BXD SERIES RHEOSTAT

Feature

- . Fused safety socket of the slidebar
- . Enclose in robust sheet metal cover
- . 100 scale division to show the resistance setting.
- . Good linearity
- . Sliding contact of coppers graphite
- . More tighter structure
- . New appearance design

Specifications

- . Max. Working Voltage: 380VAC, 400VDC
- . Resistance tolerance: $\pm 10\%$
- . Insulation resistance: $> 3 \times 10^9 \Omega$
- . Earthing resistance: $< 0.1 \Omega$
- . Rated resistance: see table



BXD160



Model	Power VA	Resistance (Ω)	Max. Current	Dimensions mm	Ceramic Pipe diameter	Weight kg
BXD160	160	1	13A	280x180x100	64mm	2.3
		3.3	7A			
		10	4A			
		33	2.2A			
		100	1.25A			
		330	0.7A			
		1000	0.4A			
BXD300	320	3300	0.22A	380x180x100	64mm	2.8
		1	18A			
		3.3	10A			
		10	5.7A			
		33	3.1A			
		100	1.8A			
		330	1.0A			
BXD600	640	1000	0.57A	480x180x100	64mm	3.5
		3300	0.31A			
		10000	0.18A			
		0.5	36A			
		1.6	20A			
		5	11.4A			
		16.5	6.2A			
BXD800	800	50	3.6A	530x180x100	64mm	4.5
		165	2A			
		500	1.1A			
		1650	0.63A			
		5000	0.36A			
		2	20A			
				

STUDENT SERIES METER

Feature

- . Compact size
- . Easy operation and stable work
- . Binding post or safety socket connection
- . Suitable for school experiment

Model	Type	Range
DCA-1	Ampere meter DC	0-50mA-500mA-5A
DCV-1	Volt meter DC	0-3V-30V-300V
DCV-2	Volt meter DC	0-300mV-3V-30V
ACA-1	Ampere meter AC	0-500mA-1A-5A
ACV-1	Volt meter AC	0-15V-150V
DCG-1	Galvano meter	$\pm 35 \mu A$

DCG-1



DCV-2



DCA-1

RHEOSTAT & STUDENT METER



Supplied by :

Test and Measurement Instruments C.C.

Tel: 0027 (011) 683 4365

www.instrumentsgroup.co.za