

**Features:**

- ▶ ABS plastic moulding
- ▶ Apertures accepting a wide range of bus bar
- ▶ CTs are ultrasonically welded and unbreakable



**Advantages:**

- ▶ Easy bus bar mounting
- ▶ Highly cost effective
- ▶ Compact in size

**Applications:**

- ▶ Switchgear
- ▶ Distribution system
- ▶ Generator sets
- ▶ Control Panels
- ▶ Control Devices
- ▶ Overload protection

**Input Specifications**

Rated Primary Current      800A to 1200A  
 Rated Secondary Output    5A/1A (Consult factory)

**Technical Specifications**

Rated Burden                    10VA (any other on request)  
 Class of Accuracy            1  
 Thermal Nominal Continuous Rated Current    1.2 times rated current continuously  
 Rated Current                 2.55x Ith  
 Thermal Short Circuit Current    60xIn  
 Insulation Class                Class E  
 Max. Operating Voltage        720V maximum  
 Insulation Test Voltage        3KV AC for 1 minute  
 Compliance Standard         VE404 and IEC185

**Environmental Specification**

Operating Temperature        20°C to 70°C  
 Storage Temperature         0° to 55°C  
 Humidity                         <95% RH

**Ordering Information**

Ordering Code	Ratio	Class	Burden (VA)
VIPS 11315940-800/5-1-10	800/5	1	10
VIPS 11315940-1000/5-1-10	1000/5	1	10
VIPS 11315940-1200/5-1-10	1200/5	1	10

**Dimensions**

