



# Coating Thickness Gauge TT211



- Designed specifically to meet the requirements of the automobile industry
- Easy calibration on zero point
- 3 kinds of adjustable resolution for different application
- High speed data collection
- Subtle design for easy hand operation
- Single testing method
- Auto switch off
- Easy conversion between metric and inch



## Technical Specifications

Operating principle		Magnetic induction
Measuring range		0~1250 $\mu$ m
3 adjustable resolution		1 $\mu$ m, 5 $\mu$ m, 10 $\mu$ m
Measuring accuracy	1 $\mu$ m	$\pm$ (3%H+1)
	5 $\mu$ m	$\pm$ (3%H+5)
	10 $\mu$ m	$\pm$ (3%H+10)
Power supply		Battery 1.5 AAA(2pcs)
Operation temperature		0 $^{\circ}$ C ~40 $^{\circ}$ C (32 $^{\circ}$ F~104 $^{\circ}$ F)
Humidity		20%RH~90%RH
Dimension		110mm $\times$ 50mm $\times$ 23mm
Weight		100g

### Standard delivery

- Main unit 1
- Calibration base set 1
- AAA 1.5 battery 2
- Waist pack for main unit 1
- Instruction manual 1
- TIME certificate 1
- Warranty card 1
- Carrying case 1

### Optional accessories

- none



Supplied by :  
Tel: 0027 (0)11 683 4365

**Test and Measurement Instruments C.C.**

[www.instrumentsgroup.co.za](http://www.instrumentsgroup.co.za)

Email:

[t.m.i@iafrica.com](mailto:t.m.i@iafrica.com)