



New Fluke 287

True-rms Electronics Logging Multimeter with TrendCapture

FLUKE®




Technical Data

The advanced, logging digital multimeter with high accuracy and TrendCapture electronics professionals can depend on.

The Fluke 287 True-rms Electronics Logging Multimeter with TrendCapture quickly documents design performance and graphically displays what happened. Its unique logging and graphing capabilities mean you no longer need to download logged readings to a PC to detect a trend. The Fluke 287 packs more accuracy and convenience into a handheld multimeter than ever before.

Equipped with new functionality

- **New** – Large 50,000 count, 1/4 VGA display with white backlight. Multiple sets of measurement information can be simultaneously displayed at the same time.



TrendCapture displays vDC logged date.

- **New** – Logging function with TrendCapture. Useful for characterizing the performance of a design or for unattended monitoring while in the field. Users can review logged readings without needing a PC.
- **New** – **i** button. On board help screens for measurement functions
- **New** – Saved measurements allow you to name and recall measurements made in the field
- **New** – Multi-lingual interface

- Multiple logging sessions possible without download
- 0.025 % basic dc accuracy
- 100 kHz ac bandwidth
- Real time clock for automatic time stamping of saved readings
- True-rms ac voltage and current for accurate measurements on complex signals or non linear loads. AC bandwidth specified to 100 kHz.
- Measure up to 10 A (20 A for 30 seconds)
- 100 mF capacitance range
- Temperature function
- Relative mode to remove test lead resistance from low ohms or capacitance measurements
- Peak capture to record transients as fast as 250 μ s
- Premium test leads and alligator clips included
- Optional FlukeView forms enables you to document, store and analyze individual readings or a series of measurements, then convert them into professional-looking documents
- Optional magnetic hanger allows you to hang the meter for easy viewing while freeing your hands to focus on the job
- Limited lifetime warranty



Supplied by :
Tel: 0027 (011) 683 4365

Test and Measurement Instruments C.C.
www.instrumentsgroup.co.za



Supplied By: Tel: (011) 683 4365
www.instrumentsgroup.co.za
Test and Measurement Instruments C.C.

FLUKE®



Specifications

Function	Range and Resolution	Basic Accuracy
DC volts AC volts	50.000 mV, 500.00 mV, 5.0000 V, 50.000 V, 500.00 V, 1000.0 V	0.025 % 0.4 % (true-rms)
DC current AC current	500.00 µA, 5000.0 µA, 50.000 mA, 400.00 mA, 5.0000 A, 10.000 A	0.15 % 0.7 % (true-rms)
Temperature (excluding probe)	-200.0 °C to 1350.0 °C (-328.0 °F to 2462.0 °F)	1.0 %
Resistance	500.00 Ω, 5.0000 kΩ, 50.000 kΩ, 500.00 kΩ, 5.0000 MΩ, 50.00 MΩ, 500.0 MΩ	0.05 %
Capacitance	1.000 nF, 10.00 nF, 100.0 nF, 1.000 µF, 10.00 µF, 100.0 µF, 1000 µF, 10.00 mF, 100.0 mF	1.0 %
Frequency	99.999 Hz, 999.99 Hz, 9.9999 kHz, 99.999 kHz, 999.99 kHz	0.005 %

Additional Functions/Features	Fluke 287
Multiple on screen displays	Yes
True-rms ac bandwidth	100 kHz
dBV/dBm	Yes
DC mV resolution	1 µV
Megohm range	up to 500 M
Conductance	50.00 nS
Continuity beeper	Yes
Battery/fuse access	Battery/fuse
Elapse time clock	Yes
Time of day clock	Yes
Min-max-avg	Yes
Peak	250 µS
Duty cycle	0.01 % to 99.99 %
Pulse width	0.025 ms, 0.25 ms, 2.5 ms, 1250.0 ms
Hold	Yes
Isolated optical interface	Yes
Auto/touch hold	Yes
Reading memory	Yes
Log to PC	Yes
Interval/event logging	Yes
Logging memory	up to 10,000 readings

Ordering information

287 True-rms Electronics
 Logging Multimeter
 with TrendCapture

Optional accessories

FVF-SC2 FlukeView® Forms
 Software with Cable
 80BK Integrated DMM
 Temperature Probe
 TLK287 Electronic Test Lead Set
 TPAK Magnetic Hanging Kit
 C280 Soft Case

General specifications

Maximum voltage between any terminal and earth ground:
 1000 V

Battery type: 6 AA alkaline
 batteries, NEDA 15A IEC LR6

Battery life: 100 hours minimum,
 200 hours in logging mode

Temperature:
 Operating: -20 °C to 55 °C
 Storage: -40 °C to 60 °C

Relative humidity: 0 to 90 %
 (0 to 37 °C), 0 to 65 % (37 °C to
 45 °C), 0 to 45 % (45 °C to 55 °C)

Electromagnetic compatibility:
 EMC EN61326-1

Vibration: Random vibration per
 MIL-PRF-28800F Class 2

Shock: 1 meter drop per IEC/EN
 61010-1 2nd Edition

Size (HxWxD): 22.2 cm x 10.2
 cm x 6 cm (8.75 in x 4.03 in x
 2.38 in)

Weight: 870.9 g (28 oz)

Supplied by :

**Test and Measurement
 Instruments C.C.**

www.instrumentsgroup.co.za
t.m.i@iafrica.com Tel: 0027 (011) 683 4365